

## NYLON PRESSURE TUBE

### IMPERIAL NYLON E1000 & E500

Esdan Nylon Pressure tubing is made from high quality nylon. It has an excellent dimensional stability, is light and saves as much as 75% in weight over rubber hoses & steel lines.

Esdan Nylon is used as a standard by many large original equipment manufacturers and industrial users in a wide range of applications. All pressure tubes are temperature & light stabilised.

Esdan Nylon is highly resistant to corrosion and heat aging. It also fully resists gasoline, diesel, fuel, oil, grease, brake fluids and other chemicals. Esdan Nylon is easy to install, the tubing can be routed inside frame rails, around corners in continuous length, thus reducing the number of couplings.



PRODUCT CODE	O.D inches	I.D inches	WALL THICKNESS	MIN. BEND RADIUS	WORKING PRESSURE @ 23°C	COIL LENGTH
<b>E-1000</b>						
63-02****	1/8"	0.088"	0.019"	2/3"	250 PSI	100m, 300m
63-03****	3/16"	0.126"	0.031"	1"	250 PSI	100m, 300m
63-04****	1/4"	0.170"	0.040"	1.5"	250 PSI	100m, 200m, 300m
63-05****	5/16"	0.212"	0.050"	2"	250 PSI	100m, 300m
63-06****	3/8"	0.260"	0.057"	2.5"	250 PSI	100m, 200m, 300m
63-08****	1/2"	0.349"	0.076"	3.5"	250 PSI	100m, 200m, 300m
<b>E-500</b>						
63-10****	5/8"	0.496"	0.064"	4-3/8"	125 PSI	50m, 100m
63-12****	3/4"	0.591"	0.080"	5.25"	125 PSI	50m, 100m
63-16****	1"	0.821"	0.089"	7"	125 PSI	M.T.O

**Esdan Plastics Pty. Ltd.**  
**525—527 Hammond Road**  
**Dandenong South**  
**Victoria 3175 Australia**

**Disclaimer**

While every reasonable care has been taken in preparation of this brochure, Esdan Plastics does not warrant that the information contained herein is without errors or omissions or suitable for your specific purpose. These specifications are to be used as a guide only, and are subject to change without notification. All safety factors are 4:1 unless stated otherwise. All information contained herein is subject to copyright and cannot be used without prior consent by ESDAN PLASTICS Pty. Ltd.